




LED Flexible Strip HTD-RGT-3528-A240 Double row Double color temperature

Description of products:

HTD-RGT-3528-A240 **Double row Double color temperature**

- Constitute by FPC, SMD3528 240LEDs(double row) per meter and UV resistant silicone resin.
- The LED beam is 125-135° flood lighting, without the shadow, high brightness in 6-8lm/LED, low therm resistance, low Light failure, in a poor environment can good work.
- 19.2W/1M, the working voltage is DC24V.
- Optional: IP20/IP65/IP68 waterproof level. Warranty optinal 1/2/3/5 years.
- Main applications:
 - Commercial and residential decoration
 - Under-counter lighting
 - Media illumination
 - Large area backlighting
 - Small to medium channel letters
 - Point-of-sale displays
 - Used for Neon or tubes replacement, etc.



*Tips:

- When we computing power should retain 20% of the allowance.
- Up to 5 Meters to use in one parallel. Screw holes on both ends to fixed, convenient and accurate.
- Advice that both ends connect DC24V power if must need 10M a string connect power supply, achieve the best use effect.



Product Chart:






— Concentrate on every lamp —

LED Flexible Strip HTD-RGT-3528-A240 Double row Double color temperature

Product Dimension Chart(Tube or IP68 width need add 2-4mm):

***Note:6LEDs/Cut/24V Power**



***Note: IP20 Height is 1.9mm/IP65 Height is 2.9mm/IP68 Height is 3.9mm**

Photometric characteristics & Main material:

Item No.	CCT	LED quantity	luminous flux (LM)	CRI	LED SPEC	PCB type	Main component
HTD-RGT-3528-A240	Double row Double CCT	240	1440-1920lm	>78-80	SMD 3528	Flexible FPC	FPC+LED (IP65: Silicone)

Basic parameters:

Item	Parameters	Units
Working voltage	DC24	V
Working power	19.2	W
Working temperature	-40~60	°C
IP grade	IP20/IP65/IP68	*
Optional light color	W/WW/CW/R/G/B/P...Can customize color	*
Beam Angle	≥120°	*
Light Source Lifespan	≥50000	hrs
Dimensions(Look above Dimension Chart)	1000×15×1.5/2.5/3.5(IP20/IP65/IP68)	mm
Net Weight/5M/Roll IP20	0.128	Kg

Connection mode (see below)

- A/.DC24V transformer connect 220V/110V AC voltage;
- B/.And then,LED strips connection DC24V output transformer.



— Concentrate on every lamp —


LED Flexible Strip HTD-RGT-3528-A240 Double row Double color temperature

Connect accessories:


Connect accessories optional:

IP20:1 to 1/1 to 4 and Connector with wire

IP65:Just 1 to 1 and Connector with wire



- UL94v-0
- 6 Ampere
- 25% Smaller
- 20AWG Wire



IP20

Non-Waterproof



IP65

Epoxy glue



IP68

Soft silicon tube mixed epoxy glue



LED Strip light identify





Concentrate on every lamp

LED Flexible Strip HTD-RGT-3528-A240 Double row Double color temperature

Package:

Conventional packing: every 5M/Roll

Carton size: 45cm*25cm*32cm.

IP20---0.128kg/roll,45Rolls/Carton/7.76kg

IP68---0.451kg/roll,25Rolls/Carton/11.25kg

IP65---0.256kg/roll,30Rolls/Carton/7.68kg


*Tips: Above package allow have 10% error

Tape feed roller




5M Led strip per roll

5M Led strip



Anti-static aluminum foil bag

45 rolls led strip



*Other style of LED Flexible strip recommend


HTD-RGT-3528-T360




HTD-RGT-335-SD240



HTD-RGT-3528-F480



HTD-RGT-2538-D120



HTD-RGT-3528-240



HTD-RGT-5730-120



HTD-RGT-3528-A240



HTD-RGT-5050-D120



Save a tree. Kindly don't print this document unless it's really necessary.